

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.

PATENT
Atty. Dkt. No. AMAT/4258/CPI/COPPER/PJS

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of:

Yezdi Dordi

Serial No.: 09/586,736

Confirmation No.: 7891

Filed: June 5, 2000

For: PROGRAMMABLE ANODE
APPARATUS AND
ASSOCIATED METHOD

Assistant Commissioner for Patents

Dear Sir:

Group Art Unit: 1741

Examiner: . Leader, W.

CERTIFICATE OF MAILING
37 CFR 1.8

First Class Mail in an envelope addressed to: Assistant
Communicator for Patents, Washington, D.C. 20231

10/10/01 Kent M. Wells
Date Signature

RESPONSE TO RESTRICTION REQUIREMENT DATED OCTOBER 2, 2001

In response to the Restriction Requirement dated October 2, 2001, having a shortened statutory period for response set to expire on November 2, 2001, please enter the following amendments and reconsider the claims pending in the application for reasons discussed below.

IN THE SPECIFICATION:

Please replace the paragraph at page 2, lines 3-13, with the following paragraph:

Deposition of a metal in electroplating is accomplished by providing an electric current to the seed layer and then exposing the seed layer to an electrolytic solution containing the metal to be deposited. One embodiment of an electroplating system that performs such metal deposition is depicted in FIG. 1. The device, known as a fountain plater 10, deposits metal on the seed layer 15 of a substrate 48. The fountain plater 10 includes an electrolyte cell 12 having a removable substrate support 14, and an anode 16 mounted to the electrolyte cell 12. A positive electrical pole 45 of the controller 42 is

Page 1

W:\PL\DOCUMENTS\APPM\4256\PTO\RESPTORR.100201.DOC

Received from < 7136234846 > at 4/23/02 4:35:43 PM [Eastern Daylight Time]

claims pending in the application for

OFFICIAL

FAX RECEIVED

APR 23 2002

GROUP 1700

3-13, with the following paragraph: